

**COMPRESSED AIR DRYER
(AIR-COOLED)
N-STANDARD TYPE
G-HIGH INLET TEMPERATURE**



Model	Port Size	Max. Capacity (Nm ³ /min)	Power Supply	Ref. Compressor (kw)	Oper. Current (A)	Full-load Current (A)	Refrigerant	Net Weight (kg)	Fan Motor (W)
J2K-08N	1/2"	0.8	220V/1Ø	0.26	1.20	1.50	R134a	25	22
J2K-10N	3/4"	1.2		0.30	1.30	1.80		37	22
J2K-15N	1"	2.4		0.50	2.13	2.73		60	50
J2K-25N	1"	3.6		0.90	4.12	4.50		66	50
J2K-40N	1-1/2"	5.5	220V/3Ø	1.00	3.50	4.70	R-22	75	93
J2K-60N	1-1/2"	8.1		1.82	6.92	8.27		94	93
J2K-75N	2"	10.6		2.20	6.00	10.0		130	125
J2K-100N	2"	15		3.00	7.80	12.3		150	125
J2K-08G	1/2"	0.8	220V/1Ø	0.26	1.20	1.50	R134a	27	46
J2K-10G	3/4"	1.2		0.30	1.30	1.80		40	46
J2K-15G	1"	2.4		0.50	2.13	2.73		66	50
J2K-25G	1"	3.6		0.90	4.12	4.50		71	50
J2K-40G	1-1/2"	5.5	220V/3Ø	1.00	3.50	4.70	R-22	80	93
J2K-60G	1-1/2"	8.1		1.82	6.92	8.27		103	93
J2K-75G	2"	10.6		2.20	6.00	10.0		144	125
J2K-100G	2"	15		3.00	7.80	12.3		160	125

Condition: Inlet temperature: 5~80°C. Environment temperature: 2~42°C. Working pressure: 0.7~1.0 Mpa
 Designate stainless steel, add **-P** (J2K-08 not suitable); Water cooled, add **-W**; High pressure type, add **-H**.